

The Modular Solution for your Precision Cleaning Task

UCMSmartLine



UCM

technology that inspires



+ Modular multi-stage wash and rinse process

+ Use of mono-, twin- or multi-frequency ultrasonics

+ Flexible transport system for optimized throughput and gentle part handling

+ Space-saving design with electrical and control technology integrated into each module

+ High-quality machine enclosure protects parts and personnel from contamination and emissions

+ Highly adaptable to changing market conditions thanks to ability to add modules at a later date

+ Short delivery times



Thin film coated parts



Precision optics



Medical components



Precision mechanics

Fields of application

- Thin film coated parts (PVD/CVD) e.g. tools, automotive parts, fittings
- Precision optics e.g. micro-optics, lenses, mirrors, prisms, masks
- Medical components e.g. implants, surgical tools, medical instruments
- Precision mechanics/precision parts e.g. aircraft, automotive parts, watches, jewellery

The Modular Solution for your Precision Cleaning Task



The UCMSmartLine is a modular, immersion-type ultrasonic system with up to nine wash and rinse stages. The versatile and well thought-out system concept offers numerous possibilities for solving individual cleaning tasks with the highest demands on component quality:



Process validation
through cleaning tests
in our test centres.

Machine concept

- Parts are agitated in wash and rinse modules, optional rotary and spinning movements
- Variable ultrasonic equipment for mono, twin and multi-frequency operation from 25 to 120 kHz
- Hot air, infrared and vacuum drying, several drying stages possible with infrared option
- Overflow circuit filtration
- Flexible transport system for handling of product carriers and baskets
- Easy creation of up to 99 different programs
- Process visualisation and fault diagnosis via IPC controller
- Connected to rinse water/ DI water re-circulation system
- Supply air filtered by HEPA filter
- Interfacing with clean rooms possible
- Closed system



- Example layout of a UCMSmartLine with 9 wet and 2 drying positions, manual loading/unloading on operator side.



Technical data

MACHINE DATA	2-in-1 module	3-in-1 module	Manual loading/ unloading station**
Dimensions (LxW)	1,100 x 1,500 mm	1,650 x 1,500 mm	650 x 1,500 mm
Height without HEPA filter	2,490 mm	2,490 mm	2,490 mm
Height incl. HEPA filter	2,790 mm	2,790 mm	2,790 mm
Weight	approx. 500 kg*	approx. 700 kg*	max. approx. 300 kg

WASH TANK/RINSE TANK

Dimensions (LxWxH)	370 x 420 x 390 mm
Tank capacity	60 l + 10 l

ULTRASONIC SYSTEM OPTIONS

Mono	25, 40, 80 kHz
Twin	25/50 & 40/80 kHz
Multi	40/80/120 kHz

PARTS CARRIER/BASKET

Dimensions (LxWxH)	250 x 300 x 210 mm
Part weight	up to 20 kg, incl. static transport rack

CONNECTIONS



Connected load	from 8.2 kW to 72.8 kW
-----------------------	------------------------

* Weight and length vary depending on system configuration

** Weight and length vary depending on loading and unloading configuration (manual or automated)



Our Locations Worldwide



© SBS Ecoclean Group • 05/2020 • EN • Subject to change. The information in this brochure contains only general descriptions or performance characteristics; these may vary depending on the application. The desired performance characteristics are only binding if they are expressly agreed upon at the time the contract is concluded.

SBS ECOCLEAN GROUP

www.ucm-ag.com

ECOCLEAN UCM MHITRAA